

:
:

. : 4/26.01.2018

μ μ -

: 17/07-09-2016 (: 75 46530 - 2), 26/ 04-10-2012 (: 4 81-70)

	μ.		1501- +	(17/07-09-2016)	
μ					
\ 22.53	.1				
22.21.02	.2	μ 50%			
\22.21.01.	.3	, μ μ . . μ μ			
\ .22.30.04	.4	(. . .), W.C., μ			
\22.04.	.5	μ μ μ μ μ			
22.45	.6	μ			
\ .22.50.	.7	(μ μ , μ . . .),			
\22.22.01. 2	.8	μ μ μ , μ			
\22.45. .2	.9	μ . . μ μ μ μ μ			
\22.45.	.10	μ			
22.15.02	.11	μ μ μ μ μ ,	15-02-01-01		
22.51	.12	μ			
22.15.01	.13	μ μ μ μ μ ,	15-02-01-01		
22.23	.14	μ	14-02-01-01		
22.20.01	.15				
\22.45.4.	.16	μ μ			

	μ.		1501- +	(17/07-09-2016)	
μ					
20.02	.17	- μ	02-03-00-00		
20.04.01	.18	E μ - μ	02-04-00-00		
01	.19		02-01-02-00		
22.30.05	.20	μ , , μ 0,50 m2 μ , 1,00 m2			
20.30	.21	μ μ μ			
20.31.02	.22	μ μ , μ			
20.40	.23				
20.41	.24	μ μ			
18.1	.25	μ , 2 3	02-06-00-00		
\ 23	.26	(μ) μ , μ μ			
\22.45.4.1	.27	μ μ			
32.01.03	.28	μ , μ μ , μ C12/15	01-01-01-00 *	μ	01-01-01-00
			01-01-02-00		
			01-01-03-00 *	μ	01-01-03-00
			01-01-04-00 *	μ μ	01-01-04-00
			01-01-05-00		
			01-01-07-00		
32.01.04	.29	μ , μ μ , μ C16/20	01-01-01-00 *	μ	01-01-01-00
			01-01-02-00		
			01-01-03-00 *	μ	01-01-03-00
			01-01-04-00 *	μ μ	01-01-04-00
			01-01-05-00		
			01-01-07-00		

	μ.		1501- +	(17/07-09-2016)	
μ					
32.01.05	.30	μ , μ , μ μ C20/25	01-01-01-00 *	μ	01-01-01-00
			01-01-02-00		
			01-01-03-00 *	μ	01-01-03-00
			01-01-04-00 *	μ μ	01-01-04-00
			01-01-05-00		
			01-01-07-00		
38.01	.31		01-04-00-00		
38.03	.32		01-04-00-00		
38.02	.33	μ	01-04-00-00		
38.20.02	.34	μ μ , B500C.	01-02-01-00 *	μ μ	01-02-01-00
38.20.03	.35	μ μ , μ μ B500C	01-02-01-00 *	μ μ	01-02-01-00
31.02.01	.36	μ μ 200 kg μ m3	01-01-01-00 *	μ	01-01-01-00
46.16.01	.37	μ μ 25x24x10 cm 10 cm μ μ	03-02-02-00 *	μ	03-02-02-00
46.01.03	.38	6x9x19 cm, μ μ 1 (μ) (μ μ)	03-02-02-00 *	μ	03-02-02-00
71.31	.39	μ - μ μ μ μ	03-03-01-00		
71.22	.40	μ μ μ μ	03-03-01-00		
49.01.01	.41	μ () μ μ μ μ μ			
\71.31	.42	μ μ μ . . . ,			
\ .10.19	.43	μ μ μ μ μ μ μ μ			
\32.01.	.44	μ C20/25 10 cm μ μ , { 100 100 }cm { 90}cm	08-07-01-03		
\32.01.	.45	μ C20/25 10 cm, 20 – 50 cm 20 cm μ { 90}cm { 100 100 }cm	08-07-01-03		
\52.61.01.	.46	μ 4.40m C14,			

	μ.		1501- +	(17/07-09-2016)	
μ					
\ 10.1	.47	45 cm. μ μ			
\56.25	.48	μ - lockers μ HPL (High Pressure Laminated) 30 50 200 . ()	03-09-01-00		
\54.46.01.	.49	13 cm , μ μ ,			
\54.46.01.	.50	13 cm , μ μ ,			
\61.05.	.51	μ μ μ			
61.30	.52				
64.01.01	.53	μ μ μ ,			
\65.02.01.	.54	μ , μ μ			
65.17.07	.55	μ μ μ μ , , μ μ , μ	03-08-03-00 *	μ μ	03-08-03-00
\65.02.01.	.56	μ , μ μ			
76.27.01	.57	μ μ - μ - 18 mm, (5 mm, 8 mm, 5 mm)	03-08-07-02		
65.05	.58	μ .	03-08-03-00 *	μ μ	03-08-03-00
\ 78.20	.59	μ μ μ (μ ,) μ			
65.17.04	.60	μ μ μ μ , , μ μ	03-08-03-00 *	μ μ	03-08-03-00
65.17.01	.61	μ μ μ μ , μ , μ	03-08-03-00 *	μ μ	03-08-03-00
\ .64.48	.62	μ μ μ 50x50 mm, (μ 3 mm, 2,36kg/m2)			
78.90	.63	μ			
11.9	.64	μ μ μ			
\61.02.	.65	μ μ , 7,32 x 2,44 m ' μ μ 120 x 105 x 2,5 mm			
\64.26.03	.66	1,50μ , μ 2ins 3,65mm μ μ 2,7mm , μ μ 5 5cm			

	μ.		1501- +	(17/07-09-2016)	
μ					
\61.22	.67	μ μ			
78.30.03	.68	μ 12 , μ , 600x600 mm	03-07-10-01		
72.16	.69	μ μ μ μ	03-05-01-00		
73.26.03	.70	15x15 cm, μ ,	03-07-02-00		
73.33.02	.71	30x30 cm μ μ , GROUP 4,	03-07-02-00		
73.16.02	.72	μ μ , 30 cm			
\ .20.20.2	.73	10 μ μ 8 .			
79.55	.74	μ - μ μ 50 mm	03-06-02-02 *	μ μ	03-06-02-02
77.83	.75	X μ μ RELIEF μ μ	03-10-02-00		
77.80.01	.76	μ μ , , μ μ μ μ , - μ	03-10-02-00		
\77.80.01	.77	μ μ & μ μ			
\77.83	.78	μ μ μ RELIEF μ μ			
77.91	.79	μ μ μ μ			
77.55	.80	μ μ μ μ	03-10-03-00		
62.10.15.01	.81	μ 12 m, μ			
08.1.1	.82	μ μ ,	10-06-07-00		
20.01.01	.83	μ μ μ μ μ 0,25 m	02-01-01-00		
04.2.2	.84	μ μ 4 μ 8 m	10-06-04-01 *	μ	10-06-04-01
01	.85	μ			

	μ.		1501- +	(17/07-09-2016)	
μ					
\73.96	.86	Quality Programme for Football Turf - μ μ (- FIFA			
9340.1	.87	μ μ 10mm2			
9340.2	.88	μ μ 16mm2			
9340.3	.89	μ μ 25mm2			
\9342	.90	Cu95mm2			
9340.4	.91	μ μ 35mm2			
\9342. .01	.92	μ μ	05-07-01-00 *	μ μ	05-07-01-00
\9344.1.10	.93		05-07-01-00 *	μ μ	05-07-01-00
\9305. .08	.94	μ μ μ	05-07-01-00 *	μ μ	05-07-01-00
60.10.01.01	.95	μ 6,00 m	05-07-01-00 *	μ μ	05-07-01-00
			05-07-02-00 *	μ μ	05-07-02-00
60.10.85.02	.96	60 x 40 cm			
60.10.85.01	.97	40 x 40 cm			
9335.1	.98	μ			
9337.3.1	.99	μ 4 2,5mm2			
9337.3.2	.100	μ 4 4mm2			
9337.3.3	.101	μ 4 6mm2			
\9337.3.9	.102	μ μ μ 3 50 + 25 mm2			
60.20.40.11	.103	μ (HDPE), μ DN 63 mm			
60.20.40.12	.104	μ (HDPE), μ DN 90 mm			
\60.20.40.13	.105	μ (HDPE), μ DN 110 mm	04-20-02-01		
60.10.40.03	.106	μ μ μ (LED), μ 50 - 80 W,	05-07-02-00 *	μ μ	05-07-02-00
\60.10.400	.107	LED 400W μμ μ 30o	05-07-02-00 *	μ μ	05-07-02-00

	μ.		1501- +	(17/07-09-2016)	
μ					
\60.10.401	.108	LED 400W μ μ μ 40o	05-07-02-00 *	μ μ	05-07-02-00
60.10.80.01	.109	μ	05-07-01-00 *	μ μ	05-07-01-00
\9350. 60	.110	μ 40 60 31			
\8840.5.2018	.111	μ 30 x 30 cm μ ' '			
\8741.100.07	.112	100 60 mm			
\1035.15.02	.113	μ μμ . 15 17 mm	04-20-01-06		
\1035.25.03	.114	μ μμ . 25 17 mm	04-20-01-06		
\1036.100.06	.115	μ μμ . 100 40 mm	04-20-01-06		
8732.1.2	.116	μμ 13,5mm			
8732.1.3	.117	μμ 16mm			
8732.1.4	.118	μμ 23mm			
\8733.1.2.06	.119	μμ μ HELIFLEX, 13.5	04-20-01-02		
\8733.1.3.06	.120	μμ μ HELIFLEX , 16	04-20-01-02		
\8733.1.4.06	.121	μμ μ HELIFLEX , 21	04-20-01-02		
\8733.1.5.06	.122	μμ μ HELIFLEX , 29	04-20-01-02		
8766.3.1	.123	μ 3 1,5mm2			
8766.3.2	.124	μ 3 2,5mm2			
8766.3.3	.125	μ 3 4mm2			
8774.6.3	.126	μ 5 4 mm2 NYY μ			
8774.6.4	.127	μ 5 6 mm2 NYY μ			
\8774.6.5.03	.128	μ NYY 5x10 mm2	04-20-02-01		
8786.1.2	.129	70 mm μ 4 mm2 3 μ			
8786.4.1	.130	100 100 mm μ 6 mm2 6			
8786.3.1	.131	90 90 mm μ 10 mm2 6			
8786.2.1	.132	80 80 mm μ 6 mm2 6			

	μ.		1501- +	(17/07-09-2016)	
μ					
8801.1.1	.133	10 μ 10 250 V			
\8811.1.03	.134	μ 10 250 V			
\8807.2.06	.135	10 μ 250 V μ -			
\8796.6 2.01	.136	J-Y(st)Y 6x2x0.6 mm			
8826.3.2	.137	μ SCHUKO 16			
\8827.1.03	.138	/ , RJ-45			
\8972.1. .01	.139	μ μ , μ μ , μ , 4x18W			
\8972.1.36.07	.140	μ μ μ μ , μ μ 1 36 W, μ μ . ,			
\8972.1.18.07	.141	μ μ μ μ , μ μ 1 18 W, μ μ . ,			
\8972.2.18.07	.142	μ μ μ μ , μ μ 2 18 W, μ μ ,			
\8982.11	.143	μ μ 100 W ,			
\8974.1	.144	μ μ , μ Ni-Cd			
8201.1.2	.145	μ 6 kg			
8204.1	.146				
\8202.3.03	.147	12kg , μ			
\8840.2.5	.148	μ 54, μ ' 106 x 75 cm			
\8840.4.4	.149	μ 54, μ ' 82 75 cm			
\8840.4.1.05	.150	μ 54, μ ' 50 35 cm	05-07-02-00 *	μ μ	05-07-02-00
8880.3.2	.151	40 5 SIEMENS			
8880.3.3	.152	63 5 SIEMENS			

	μ.		1501- +	(17/07-09-2016)	
μ					
8880.3.4	.153	80 5 SIEMENS			
\8880.1.1	.154	μ 25 5 SIEMENS,			
\8880.2.1.09	.155	25 5 SIEMENS,			
\8880.3.5	.156	100 5 SIEMENS,			
\8880. .25.03	.157	25			
\8880. .40.03	.158	40	05-07-02-00 *	μ μ	05-07-02-00
\8880. .63.03	.159	63			
\8880. .80	.160	80			
\8896.11.02	.161	25 μ μ	05-07-02-00 *	μ μ	05-07-02-00
\8910.25 .03	.162	μ 16(μ) EZ-SIEMENS 25 A μ			
\8910.35 .03	.163	μ 16(μ) EZ-SIEMENS μ 35 A	05-07-02-00 *	μ μ	05-07-02-00
\8910.50 .03	.164	μ 16(μ) EZ-SIEMENS μ 50 A			
\8910.63 .03	.165	μ 16(μ) EZ-SIEMENS 63 A μ	05-07-02-00 *	μ μ	05-07-02-00
8915.1.1	.166	μ WL-SIEMENS μ μ 6			
8915.1.2	.167	μ WL-SIEMENS μ μ 10			
8915.1.3	.168	μ WL-SIEMENS μ μ 16			
8915.1.4	.169	μ WL-SIEMENS μ μ 20			
8915.1.5	.170	μ WL-SIEMENS μ μ 25			
\8919.1.06	.171	(Aμ μ - μ - μ)			
\8924.1.01	.172	μ 500 V	05-07-02-00 *	μ μ	05-07-02-00
\8041.15	.173	drawn), DIN-1786/ -17671 μ (solid 1 mm μ 15 mm			

	μ.		1501- +	(17/07-09-2016)	
μ					
\8041.20	.174	drawn), DIN-1786/ -17671 μ (solid 20 mm μ 1 mm			
\8041.25	.175	drawn), DIN-1786/ -17671 μ (solid 25 mm μ 1 mm			
\8041.32	.176	drawn), DIN-1786/ -17671 μ (solid 32 mm μ 1,50 mm			
\8115.21.1	.177	μ 1/2 ins , μ μ 1/4 ,			
\8129. .01	.178	A μ μ (μ , μ)			
\8131.1	.179	B (μ μ 1/2 ins)			
8151.1	.180				
\8151. . .16	.181				
\8153.1.	.182	μ μ			
\8160.2	.183	35 40 cm			
\8160.2.03	.184	42 56 cm			
\8168.1.	.185	4 mm μ			
\8174.1.	.186				
8179.2	.187	μ μ μ μ			
\8179.3.	.188	μ μ μ μ			
\8257.200.	.189	μ , 200lt			
\8303. . .	.190	μ			
\8303. . .	.191				
8178	.192				
8138.1.2	.193	(μ 1/2 ins)			
8141.2.2	.194	μ (μ) μ - , μ μ 1/2 ins μ			
8141.4.3	.195	μ (μ) μ - , μ μ 1/2 ins μ			
\8602. .1.08	.196	, 7			

	μ.		1501- +	(17/07-09-2016)	
μ					
\8063.	.218	() μ 6 10 cm P.V.C.			
\8064.1.03	.219	μ			
01.1	.220	μ	05-03-03-00 *	μ	05-03-03-00
μ					
1407					
1444		μ μ 600 kg			
1447		μ μ 400 kg			
1502		μ μ 250			
2121		μ μ μ			
3211		μ 200 kg μ , 0,7 2,5 3 cm			
3213		μ C12/15 300 kg μ , 0,7 2, 5 3 cm			
4623.2		μ μ (μ)			
7122		μ μ μ 600Kg			
\8072.1.01		μμ o			
\20.31.02		μ μ , μ			
22.21.01					
22.22.01		μ μ			
22.50					
22.53					
\22.04		μ	14-02-02-01		
\22.45		μ			
33.01.02		μ μ μ μ			
38.14.02		425 mm μ μ μ			
41.01			08-03-02-00		

	μ.		1501- +	(17/07-09-2016)	
μ					
52.61.01		μ , 6,00 m μ μ ()			
54.46.01		13 cm μ μ ,	03-08-01-00		
56.25		μ μ , μ μ	03-09-01-00		
61.05		160 mm			
61.22		- μ			
64.26.03		μ μ , 2 "			
64.47		μ μ μ			
64.48		μ μ μ μ			
65.02.01.01		μ μ , μ μ μ , μ μ	03-08-03-00 *	μ μ	03-08-03-00
73.96		μ (PVC)	03-07-06-02		
77.97		μ			
\77.83		X μ μ RELIEF μ μ	03-10-02-00		
78.20		μ μ μ , μ			
23		μ μ - μ			
10.19		μ μ μ μ μ			
10.1		μ - μ , μ	10-02-02-01 *		10-02-02-01

, 26/01/2018

μ

, 26/01/2018